



**PART NUMBER:** 1494-6-2N-DP1656  
**TITLE:** 2 INPUTS UHF / DTV DOUBLE BRIDGE COMBINER



Tunable within whole UHF range.  
 For 6,7,8 MHz channel bandwidth.  
 Different connectors on request.



<b>Input narrowband:</b>	EIA 7/8"
<b>Input broadband:</b>	EIA 7/8"
<b>Output:</b>	EIA 1 5/8"
<b>Maximum operating temp. (C°):</b>	70
<b>Weight (kg):</b>	50

<b>DVB-T @ 8 MHz</b>	
Frequency range (MHz)	470 ÷ 862
Bandwidth (MHz)	6 ÷ 8
Insertion loss (dB) @ fo	< 0.6
Insertion loss (dB) @ fo ±3.805 MHz	< 1.7
Attenuation @ fo ± 4.2 MHz (dB)	> 12
Attenuation @ fo ± 6 MHz (dB)	> 24
Attenuation @ fo ± 12 MHz (dB)	> 36
Broadband insertion loss (dB)	> 0.2
Return loss (dB)	> 26
Insulation (dB)	> 30
Input/output impedance (Ohm)	50
Min. distance between channels	1 guard channel
Narrowband maximum power (W)	1500 DTV
Maximum output power (W)	5000 DTV
Maximum group delay variation (ns)	300

